

ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVENUE, SUITE 3
RONKONKOMA, NEW YORK 11779-7348
PHONE: (631) 580-3191 • FACSIMILE (631) 580-3195

PRINCIPALS

J. DRISCOLL
B. GALLAGHER
T. KLUENDER
G. NEUSCHWENDER

E. DETWEILER
E. IVANS
R. KLUENDER
G. MENEGIO
J. SPILLETT

March 9, 2015

Town of Islip Parks & Recreation
Ms. Inez Birbiglia
50 Irish Lane
East Islip, NY 11730

RE: Roberto Clemente Park

Dear Ms. Birbiglia,

Attached please find the results for the asbestos air sampling that was conducted in the Roberto Clemente Park, located at 400 Broadway in Brentwood, NY. There were three sample dates in February. The first week in February sampling was cancelled to due to inaccessibility. Please feel free to call me with any questions.

Sincerely,



Glenn Neuschwender
President

ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779
+ PHONE (631) 580-3191 + FAX (631) 580-3195


ELAP # 11681; NVLAP Lab Code 200531-0

TEM AIR SAMPLE RESULTS

CLIENT:	Town of Islip	SAMPLE DATE:	2/1/2015
PROJECT NAME:	Roberto Clemente Park	DATE RECEIVED:	2/1/2015
AREA:	Perimeter Monitoring	SAMPLE TYPE:	Ambient
JOB #:	11114	SAMPLER:	Edik Ivans
PAGE #:	1 of 2	CUSTODY #:	12798

Sample #	Sample Location	Start	End	Run Time Minutes	Flow Rate Average	Volume Liters	Total Asbestos Structures	Type	# of structures > 5µ	# of structures >0.5µ <5µ	Filter Conc. S/mm ²	Sensitivity S/cc	Air Conc. S/cc
T1 IWA	North Perimeter	9:25	11:25	120	10	1200	0		0	0	0	.0043	<.0043
T2 IW	North Perimeter	9:25	11:25	120	10	1200	0		0	0	0	.0043	<.0043
T3 IWA	Northeast Perimeter	9:29	11:29	120	10	1200	0		0	0	0	.0043	<.0043
T4 IWA	Northeast Perimeter	9:29	11:29	120	10	1200	0		0	0	0	.0043	<.0043
T5 IWA	East Perimeter	9:33	11:33	120	10	1200	0		0	0	0	.0043	<.0043
T6 IWA	East Perimeter	9:33	11:33	120	10	1200	0		0	0	0	.0043	<.0043
T7 IWA	Southeast Perimeter	9:37	11:37	120	10	1200	0		0	0	0	.0043	<.0043
T8 IWA	Southeast Perimeter	9:37	11:37	120	10	1200	0		0	0	0	.0043	<.0043
T9 IWA	Northwest Perimeter	11:45	13:45	120	10	1200	0		0	0	0	.0043	<.0043

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, µ=micrometer
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by: 

Date Analyzed: 2/13/2015

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).
Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).
The data pertaining to these calculations can be found on the Asbestos Count Sheet.
The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.
The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.
A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779
+ PHONE (631) 580-3191 + FAX (631) 580-3195


ELAP # 11681; NVLAP Lab Code 200531-0

TEM AIR SAMPLE RESULTS

CLIENT:	Town of Islip	SAMPLE DATE:	2/1/2015
PROJECT NAME:	Roberto Clemente Park	DATE RECEIVED:	2/1/2015
AREA:	Perimeter Monitoring	SAMPLE TYPE:	Ambient
JOB #:	11114	SAMPLER:	Edik Ivans
PAGE #:	2 of 2	CUSTODY #:	12798

Sample #	Sample Location	Start	End	Run Time Minutes	Flow Rate Average	Volume Liters	Total Asbestos Structures	Type	# of structures > 5µ	# of structures >0.5µ <5µ	Filter Conc. S/mm ²	Sensitivity S/cc	Air Conc. S/cc
T10 IWA	Northwest Perimeter	11:45	13:45	120	10	1200	0		0	0	0	.0043	<.0043
T11 IWA	West Perimeter	11:48	13:48	120	10	1200	0		0	0	0	.0043	<.0043
T12 IWA	West Perimeter	11:48	13:48	120	10	1200	0		0	0	0	.0043	<.0043
T13 IWA	Southwest Perimeter	11:53	13:53	120	10	1200	0		0	0	0	.0043	<.0043
T14 IWA	Southwest Perimeter	11:53	13:53	120	10	1200	0		0	0	0	.0043	<.0043
T15 IWA	South Perimeter	11:57	13:57	120	10	1200	0		0	0	0	.0043	<.0043
T16 IWA	South Perimeter	11:57	13:57	120	10	1200	0		0	0	0	.0043	<.0043
T17	Sealed Blank						0		0	0	0		
T18	Opened Field Blank						0		0	0	0		

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, µ=micrometer
≤less than, >greater than, Flow Rate in liters per minute

Analyzed by: 

Date Analyzed: 2/13/2015

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).
Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).
The data pertaining to these calculations can be found on the Asbestos Count Sheet.
The air filter concentration relates only to air filter content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.
The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.
A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779
+ PHONE (631) 580-3191 + FAX (631) 580-3195


ELAP # 11681; NVLAP Lab Code 200531-0

TEM AIR SAMPLE RESULTS

CLIENT:	Town of Islip	SAMPLE DATE:	2/20/2015
PROJECT NAME:	Roberto Clemente Park	DATE RECEIVED:	2/20/2015
AREA:	Perimeter Monitoring	SAMPLE TYPE:	Ambient
JOB #:	11114	SAMPLER:	Edik Ivans
PAGE #:	1 of 2	CUSTODY #:	12875

Sample #	Sample Location	Start	End	Run Time Minutes	Flow Rate Average	Volume Liters	Total Asbestos Structures	Type	# of structures > 5µ	# of structures >0.5µ <5µ	Filter Conc. S/mm ²	Sensitivity S/cc	Air Conc. S/cc
T1 IWA	North Perimeter	9:25	11:25	120	10	1200	0		0	0	0	.0043	<.0043
T2 IWA	North Perimeter	9:25	11:25	120	10	1200	0		0	0	0	.0043	<.0043
T3 IWA	Northeast Perimeter	9:28	11:28	120	10	1200	0		0	0	0	.0043	<.0043
T4 IWA	Northeast Perimeter	9:28	11:28	120	10	1200	0		0	0	0	.0043	<.0043
T5 IWA	East Perimeter	9:31	11:31	120	10	1200	0		0	0	0	.0043	<.0043
T6 IWA	East Perimeter	9:31	11:31	120	10	1200	0		0	0	0	.0043	<.0043
T7 IWA	Southeast Perimeter	9:34	11:34	120	10	1200	0		0	0	0	.0043	<.0043
T8 IWA	Southeast Perimeter	9:34	11:34	120	10	1200	0		0	0	0	.0043	<.0043
T9 IWA	Northwest Perimeter	11:40	13:40	120	10	1200	0		0	0	0	.0043	<.0043

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, µ=micrometer
<=less than, >greater than, Flow Rate in liters per minute

Analyzed by: 

Date Analyzed: 2/24/2015

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).
Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).
The data pertaining to these calculations can be found on the Asbestos Count Sheet.
The air filter concentration relates only to air fiber content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.
The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.
A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779
+ PHONE (631) 580-3191 + FAX (631) 580-3195


ELAP # 11681; NVLAP Lab Code 200531-0

TEM AIR SAMPLE RESULTS

CLIENT:	Town of Islip	SAMPLE DATE:	2/20/2015
PROJECT NAME:	Roberto Clemente Park	DATE RECEIVED:	2/20/2015
AREA:	Perimeter Monitoring	SAMPLE TYPE:	Ambient
JOB #:	11114	SAMPLER:	Edik Ivans
PAGE #:	2 of 2	CUSTODY #:	12875

Sample #	Sample Location	Start	End	Run Time Minutes	Flow Rate Average	Volume Liters	Total Asbestos Structures	Type	# of structures > 5µ	# of structures >0.5µ <5µ	Filter Conc. S/mm ²	Sensitivity S/cc	Air Conc. S/cc
T10 IWA	Northwest Perimeter	11:40	13:40	120	10	1200	0		0	0	0	.0043	<.0043
T11 IWA	West Perimeter	11:43	13:43	120	10	1200	0		0	0	0	.0043	<.0043
T12 IWA	West Perimeter	11:43	13:43	120	10	1200	0		0	0	0	.0043	<.0043
T13 IWA	Southwest Perimeter	11:46	13:46	120	10	1200	0		0	0	0	.0043	<.0043
T14 IWA	Southwest Perimeter	11:46	13:46	120	10	1200	0		0	0	0	.0043	<.0043
T15 IWA	South Perimeter	11:49	13:49	120	10	1200	0		0	0	0	.0043	<.0043
T16 IWA	South Perimeter	11:49	13:49	120	10	1200	0		0	0	0	.0043	<.0043
T17	Sealed Blank						0		0	0	0		
T18	Opened field Blank						0		0	0	0		

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, µ=micrometer
≤less than, >greater than, Flow Rate in liters per minute

Analyzed by: 

Date Analyzed: 2/24/2015

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).
Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).
The data pertaining to these calculations can be found on the Asbestos Count Sheet.
The air filter concentration relates only to air filter content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.
The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.
A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779
+ PHONE (631) 580-3191 + FAX (631) 580-3195


ELAP # 11681; NVLAP Lab Code 200531-0

TEM AIR SAMPLE RESULTS

CLIENT:	Town of Islip	SAMPLE DATE:	2/25/2015
PROJECT NAME:	Roberto Clemente Park	DATE RECEIVED:	2/26/2015
AREA:	Perimeter Monitoring	SAMPLE TYPE:	Ambient
JOB #:	11114	SAMPLER:	Driscoll / Africano
PAGE #:	1 of 2	CUSTODY #:	12908

Sample #	Sample Location	Start	End	Run Time Minutes	Flow Rate Average	Volume Liters	Total Asbestos Structures	Type	# of structures > 5µ	# of structures >0.5µ <5µ	Filter Conc. S/mm ²	Sensitivity S/cc	Air Conc. S/cc
T01 IW/A	SW perimeter	11:10	13:10	120	10	1200	0		0	0	0	.0043	<.0043
T02 IW/A	SW perimeter	11:11	13:11	120	10	1200	0		0	0	0	.0043	<.0043
T03 IW/A	W perimeter	11:12	13:12	120	10	1200	0		0	0	0	.0043	<.0043
T04 IW/A	NW perimeter	11:19	13:19	120	10	1200	0		0	0	0	.0043	<.0043
T05 IW/A	NW perimeter	11:20	13:20	120	10	1200	0		0	0	0	.0043	<.0043
T06 IW/A	N perimeter	11:20	13:20	120	10	1200	0		0	0	0	.0043	<.0043
T07 IW/A	SE perimeter	11:24	13:28	124	10	1240	0		0	0	0	.0042	<.0042
T08 IW/A	SE perimeter	11:25	13:28	123	10	1230	0		0	0	0	.0042	<.0042
T09 IW/A	S perimeter	13:16	15:16	120	10	1200	0		0	0	0	.0043	<.0043

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, µ=micrometer
 <=less than, >greater than, Flow Rate in liters per minute

Analyzed by: 

Date Analyzed: 3/4/2015

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).
 Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).
 The data pertaining to these calculations can be found on the Asbestos Count Sheet.
 The air filter concentration relates only to air filter content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.
 The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.
 A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.

ENVIROSCIENCE CONSULTANTS, INC.

2150 SMITHTOWN AVE. + RONKONKOMA, NY 11779
+ PHONE (631) 580-3191 + FAX (631) 580-3195


ELAP # 11681; NVLAP Lab Code 200531-0

TEM AIR SAMPLE RESULTS

CLIENT:	Town of Islip	SAMPLE DATE:	2/25/2015
PROJECT NAME:	Roberto Clemente Park	DATE RECEIVED:	2/26/2015
AREA:	Perimeter Monitoring	SAMPLE TYPE:	Ambient
JOB #:	11114	SAMPLER:	Driscoll / Africano
PAGE #:	2 of 2	CUSTODY #:	12908

Sample #	Sample Location	Start	End	Run Time Minutes	Flow Rate Average	Volume Liters	Total Asbestos Structures	Type	# of structures > 5µ	# of structures >0.5µ <5µ	Filter Conc. S/mm ²	Sensitivity S/cc	Air Conc. S/cc
T10 IWA	S perimeter	13:16	15:16	120	10	1200	0		0	0	0	.0043	<.0043
T11 IWA	Center of park	13:17	15:17	120	10	1200	0		0	0	0	.0043	<.0043
T12 IWA	N perimeter	13:23	15:23	120	10	1200	0		0	0	0	.0043	<.0043
T13 IWA	NW perimeter	13:24	15:24	120	10	1200	0		0	0	0	.0043	<.0043
T14 IWA	NW perimeter	13:25	15:25	120	10	1200	0		0	0	0	.0043	<.0043
T15 IWA	East perimeter	13:31	15:31	120	10	1200	0		0	0	0	.0043	<.0043
T16 IWA	East perimeter	13:32	15:32	120	10	1200	0		0	0	0	.0043	<.0043
T17	Scaled blank						0		0	0	0		
T18	Open field blank						0		0	0	0		

S=Asbestos structures, cc=cubic centimeters, mm=millimeters, µ=micrometer
 <=less than, >greater than, Flow Rate in liters per minute

Analyzed by: 

Date Analyzed: 3/4/2015

Samples were analyzed using Philips 400T Transmission Electron Microscope. Asbestos identification is determined by morphology, visual Selected Area Electron Diffraction (SAED), and Elemental Analysis using an Energy Dispersive X-ray Analyzer (EDAX).
 Concentration on the filter is calculated by taking the number of asbestos structures and dividing by the area analyzed. Air concentration is calculated by multiplying the effective filter area (EFA) by the filter concentration and then dividing by the volume of air collected in cubic centimeters (cc).
 The data pertaining to these calculations can be found on the Asbestos Count Sheet.
 The air filter concentration relates only to air filter content. When samples are submitted by an outside agency for analysis, Enviroscience Consultants, Inc. can only guarantee the accuracy of the filter concentration. This report may not be reproduced without the express permission of Enviroscience. This report cannot be used to claim endorsement of products by NVLAP or any agency of the U.S. Government.
 The samples collected in the response action area demonstrated a filter concentration of asbestos less than seventy structures per square millimeter. This response action is considered complete according to EPA 40 CFR 763.
 A result of zero structures per square millimeter is only applicable to the area analyzed. Test results only reflect conditions at the time the samples were taken.